



Architectural Grade High Power 9 Watt Dimmable Led Replacement Lamp Produces 50 Watts of Halogen Light Dimming to 10%

LM-79 and LM-80 Tested

- Robust electronics on board
- Proprietary optics deliver light to the task
- Instant ON, no warm up, no flicker
- May be controlled by peripheral systems and sensors
- Five year hassle free warranty
- Generous beta test programs
- Reduced waste – contractor and earth-friendly packaging for roll-outs and projects
- Finishes: White, Black
- Suitable for damp locations

Life Rating Reduced +/- 15% When Used in IC Housings.
Do Not Use in Enclosed Fixtures.

*Compatible dimmer models:
Lutron D-600PH, DVW-600PH, DVW-603PGH, S-603PGH & CN-600;
Leviton Slide Dimmer 6631 & Push Dimmer 6681

Family	Product	Beam	Color Temp	Finish
DL	P20G	20	27K 30K	WH BL

Beam Angle	20°	
Power Consumption (Max)	9 Watts	
Equivalent Source	50W	
Power Factor	>0.80	
Dimming Range*	10-100%	
Color Temperature	2700K (Warm White)	3000K (Natural White)
CRI	80+	
Lumen Output (Typ)	415	435
Lumens/Watt	45	47
CBCP (Typ)	1545	1965
Operating Temp	-4~104°F ; 20%~80% RH	
Storage Temp	-22~140°F ; 15%~85% RH	
AC Input Voltage	120 Volts	
Lumen Maintenance	L70 >50,000 Hours	
Environmental	Contains no lead or mercury No UV or IR emmissions	
Warranty	5 years	
Use	Indoor applications	
Weight	6.25 ounces ±0.2	
Dimensions	2.5"W x 3.25"H	
Base	E26	

